

MEDITECH

IP12V
VETERINARY INFUSION PUMP

MAIN FEATURES

- Bright color and large LCD touch screen
- Small size, easy to carry and economical to transport
- Compatible with infusion tubes of any standard
- Three infusion modes for your selection
- KVO & Bolus function
- Intelligent pressure detection & occlusion detection(adjustable on 3 levels)
- Audiovisual alarms,shockproof and waterproof
- Autosave previous infusion record
- Heating function
- Real time display



INFUSION PUMP FOR VETERINARY USE

◎ Technical Parameters

Infusion mode	Rate mode, Drip mode, Trace mode
Infusion set	Any brand of infusion set
Infusion accuracy	± 5%
Infusion rate range	Normal mode:1~1200ml/h, increment 1 ml/h; Trace mode:0.1-99.9ml/h, increment 0.1ml/h
KVO rate	1-8ml/h
P /Bolus rate urge	300-1200ml/h
Volume To Be Infused (VTBI)	1~9999 ml
Air Bubble detection	Ultrasound sensor detection of air bubble
Occlusion detection	Occlusion pressure detection adjustable on 3 levels
Alarm	Over, Low battery, Air, Occlusion., AC power failure, Door open, Time waited out, Error, Countdown
Displayed information	AC power connection, Power, Volume, Door open, Tube, Occlusion level, Air, Occlusion., Low., Over, Error, Time waited out, Real time Infusion rate, VTBI, Volume infused
Power supply	AC 100-220V, 50-60Hz
Battery	Rechargeable lithium battery, 7.4 V, 2400mAh; Can work continuously for 3.5 hours at the rate of 25ml/h .
Dimensions	135x90x135 mm (L×W×H)
Weight	≤1.5Kg
Classification	Class II, BF type
Waterproof level	IPX3

TOOTOO MEDITECH CO., LTD.
Address: RM 607, HAIHANG CITY BUSINESS CENTER, LONGGANG, SHENZHEN, CHINA.
Tel: +86-755-28306385 Email:info@newtootoo.com Web: www.newtootoo.com